

BEAM CONSOLIDATED **G**accessories™

JOINT PAPER TAPE



DESCRIPTION

The Joint Paper Tape is used with Gcoat™ / Ccoat™ compound in drywall systems to reinforce jointing between boards, and to resist stretches and cracks. The Joint Paper Tape is made of fibred tape, characterized by its high strength and tearing resistance.

FEATURES

- High Flexibility
- Easy installation
- Resists edge cracking
- Excellent solution for bulkheads

TECHNICAL DATA

SPECIFICATIONS	UNIT	VALUE
Material		Highly flexible paper
Roll Width	mm	50
Roll Length	m	75 -150
Packaging		Poly bag / PE Shrink - Packed
Color		Ivory

METHOD OF USE

- Ensure that the surface is clean from dust and other impurities. The work site should be adequately ventilated to facilitate drying of materials.
- Clean the surfaces from the dust and other impurities.
- Cover the head of the screws with a thin layer of compound.
- Apply tape along the joints, then apply the first layer of Gcoat™ / Ccoat™ to extend 50mm beyond both sides (100mm width in total).
Embed the tape in Gcoat™ / Ccoat™ to reinforce the joints between the panels.
- Smooth the first layer once it's dried using appropriate sanding paper then apply a second layer of the compound with a width of 200mm.
- Smooth the second layer and apply a third thin layer of Gcoat™ / Ccoat™ with a width of 300mm.

